



DVCS[®] 3

4 Channel Video Processor

- Support 4 channel CVBS or S-Video Input
- Supports four free windows simultaneously for each channel
- Supports Multicasting Windows
- Supports Power-on-Ethernet+



4K Display Wall



Specifications

| Input | |
|------------------------------|--|
| Interface | Mini-DSUB |
| Channels | 4 |
| Format | PAL,NTSC |
| Color Depth | 8 bit |
| Network | |
| Ethernet | 1000MB network with redundancy |
| Power-on-Ethernet | Support POE+ |
| Protocol | DHCP, UDP, TCP/IP |
| IP Address | Static IP, Automatic IP |
| Image Processing | |
| Image Processing | 3rd-gen DVCS Engine |
| | 3-2/2-2 Pull Down |
| | 3D Comb Filter |
| | 3D Noise Reduction |
| | High tap filter for image scaling |
| | Max. 60 fps image processing |
| | Support 4 windows simultaneously |
| Support windows multicasting | |
| Control | |
| Server | DVCS Manager V4.0 or above Windows Server 2008 X64 or above |
| Client | IE 8.0 or above |
| LED | |
| Power | LED x1, Green |
| Status | LED x1, Red/Green |
| Network | LED x1, Red/Green |

| Fan | LED x1, Red/Green |
|--------------------------------|------------------------------|
| Interface | |
| Video | 1*Mini-DSUB |
| Serial Port | RS-232 x1 (DB-9) |
| Network | RJ-45 x2 |
| Reset | 1 |
| Power | 1 |
| Enclosure | |
| Material | Metal (Black) |
| H x W x D | 34.5 x 210 x 197.5 mm |
| Weight | 1.0 Kg |
| Shipping Weight | 1.5 Kg |
| Operation Range | |
| Temperature | 0~40°C |
| Humidity | 10~90%, non-condensing |
| Altitude | 16,400 feet (5000m) or below |
| Electrical Requirements | |
| Input | Mini-jack, +12V DC Adaptor |
| Frequency | 50/60 Hz |
| Power Consumption | Max 18 Watts |
| Accessories | |
| DC Adapter | 1 |
| 8*BNC-F to Mini-DSUB Converter | 1 |
| Reliability | |
| MTBF | >100,000 hours |

※ All specifications are subject to change without prior notice. Ver:1.2018

Website: www.deltadisplays.com | Contact Us: vw.sales@deltadisplays.com

