



LED Display Controller

DC-500 & 600

- Supports multiple input resolutions : 2048x1152 · 1920x1200 · 2560x960;
- USB Port for easy access to software control
- 18 bit gray scale processing and presentation;
- HDMI / External audio input
- Front viewable power and signal indicators
- Support redundancy and multiple LED wall sources
- 1U space rack mountable unit



DC-500 & 600

LED controller Sending unit is the next step from our base sending unit. It is a single space rack mount unit, which offers two or four CAT 5 outputs. Allowing for more redundancy and security. This unit can be accessed using a PC laptop and Delta control software.



Specifications

Product Name	DC- 500	DC- 600
Control port	RS232	USB
Video Input	DVI	HDMI / DVI
Signal Output	RJ45/Fiber-optic	
Resolution	2.3million pixels	
Maximum width output	2048 pixels	
Maximum height output	1200 pixels	
Power Input (AC)	AC 100 ~ 240V	
Dimension (L x H x D)	482.6 x 44.45 x 250 mm	
Weight	2.9Kg	
Audio Input	Yes	
Operation Voltage	4.7~6V	
Operation Current	0.45~0.7A	
Operation Temperature	-20~75°C	
Operation Humidity	0%-95%	
Storage Temperature	-20~75°C	
Storage Humidity	0%-95%	
USB Cable	1.5M	
DVI Cable	1.5M	